

LITECRAFT®

PAR 64 AT10



The PAR 64 AT3, too, has a worthy successor. Thanks to an extensive redesign, whilst the dimensions are unchanged and the power consumption only marginally increased, the light output of the PAR 64 AT10 is double that of its predecessor. Furthermore, this model offers RGB + amber colour mixing, by which means the mixable colour spectrum has been considerably expanded.

The redesign has also brought detailed enhancements that make the PAR 64 AT10 even more user-friendly. The new Y bracket is not only compact and light but can also safely be relied on whether the fixture is suspended or used in a standing position.

Inadvertent adjustment of the bracket position is no longer possible. In addition, the power cable has been replaced by PowerCon sockets with a loop-through function.

As is the case with all LITECRAFT models, this fixture boasts a two-line LCD that makes it possible for anyone to operate the device correctly without needing a user manual.

PAR 64 AT10, black **Order code: 161482**
PAR 64 AT10, silver **Order code: 161483**

Optical System
 Optics Changeable Optics
 Beam Angle 25°

LED Lightsources
 LEDs 18x 10 W Multicolour LEDs
 Colours 18x red, 18x green, 18x blue, 18x amber
 LED Lifetime > 50.000 hours
 Colour Mixing System RGBA

Temperature Zones
 Ambient Temperature 0°/+35° C
 Operating Temperature max. 55° C
 Cooling Fan

Controlling & Programming
 Protocol USITT DMX 512
 DMX 512 Channels 1/2/3/4/8 (5 Modes)
 Internal Memory Audio/Stand Alone-Programms
Pre-Programmed Colours, Master-/Slave
 Menu Display LCD 8 digit, 2 lines
 DMX 512 Connection XLR 5 pin

Technical Details
 Mains 90-264 V, 47-63 Hz
 Power Consumption 0,5 A at 230 V

Housing
 Material Aluminium
 Colour black/silver
 Protection Class IP 20

Measurements/Weight
 Measurements (L x W x H) 30,1 x 26,9 x 40,8 cm
 Weight 4,8 kg
 Assembling compact Y-yoke
for hanging and floor standing mounting

Special Features

- 10 W LED Chips
- Original italian KHATOD lenses
- RGBA in one lens
- More wide colour range due to additional amber LED
- Brilliant colour mixing
- Smooth dimming
- Pre-programmed colour macros
- Pre-programmed colour chasers
- Stand-alone RGBA colour setting
- Hold on last memory
- Easy menu structure with LC-display
- Fixture hour counter
- Default set option
- XLR 5 pin In/Out
- NEUTRIK PowerCon In/Out
- Compact Y-yoke for hanging and floor standing mounting
- Master-/Slave-Mode

Accessory Inclusive
 NEUTRIK PowerCon-cable with Schuko plug
 Compact Y-yoke for hanging and floor standing mounting

Accessory optional
http://shop.lmp.de/de_DE/002000000/002390000/002390100/00161482.html